

LINN LINTO DIRECT COUPLED PRECISION PHONO PREAMPLIFIER

The Linto Direct Coupled Precision Phono Preamplifier is the ultimate source component for those who have a vinyl collection. The Linto is designed to carefully nurture, protect and amplify every fine, sensitive detail of the music signal at the retrieval and amplification stage.

Coupling the turntable source components to the control elements in the most faithful and direct way possible, this moving coil cartridge preamplifier can be used with virtually any high quality turntable or preamplifier. The Linto has a choice of two gain settings so it can be used with both low and higher output moving coil cartridges.

Innovative circuit design and precision surface mount technology has enabled direct connections between the Linto input sockets and its amplified output to ensure the cleanest possible transfer of the vital information signal generated by the moving coil cartridge. The Linto is powered by the latest Linn proprietary Brilliant Switch Mode Power Supply technology. These silent power supplies with their extensive internal shielding, make this purpose-built, specialist phono preamplifier the ultimate product upgrade for vinyl information retrieval.

Advanced surface mount electronic manufacturing technology, skill and expertise maximises signal fidelity with higher quality soldered connections and ultra short signal paths. Surface mount circuitry also minimises interference, noise pick-up, inter component coupling, microphony and radio breakthrough, while enhancing component joint integrity, longevity and total product reliability and lifespan.

The Linto demonstrates Linn's continued commitment to our most enthusiastic music loving customers and provides them with a new reference standard for the reproduction of their recorded music. Designed to match other Linn Hi-Fi components, the Linto is launched to mark and celebrate the Silver Anniversary of the Linn Sondek LP12 Transcription Turntable.

Retail Price: £850

For more information please contact Linn Products Ltd
customer services on Freephone 0500 888909

LINTO DIRECT COUPLED PRECISION PHONO PREAMPLIFIER TECHNICAL SPECIFICATIONS

Type:	Moving Coil Phono Preamplifier
Audio Inputs:	1 pair of Gold Plated RCA Phono Sockets
Audio Outputs:	2 pairs of Gold Plated RCA Phono Sockets
Input Level:	150 uV Nominal on High Gain Setting 480 uV Nominal on Low Gain Setting
Input Impedance:	150 Ohms // 4.7 nF
Gain:	High Gain: 64 dB @ 1kHz (x 1600) Low Gain: 54 dB @ 1kHz (x 500)
Maximum Input:	High Gain: 6.7mV peak at 1kHz Low Gain: 19 mV peak at 1 kHz